



Bestellnummer	øD	øA	T	øG	Tkø	Fase	kg
298 035 072 060	35	72	10,0	ø 7 x 4	60	3x45°	0,23
298 040 080 065	40	80	12,0	ø 9 x 4	65	3x45°	0,33
298 042 089 070	42	89	12,0	ø 9 x 4	70	3x45°	0,43
298 045 095 075	45	95	12,0	ø 9 x 4	75	3x45°	0,49
298 050 109 087	50	109	12,5	ø 11 x 4	87	4x45°	0,66
298 055 123 100	55	123	14,5	ø 11 x 4	100	4x45°	1,03
298 060 128 105	60	128	14,5	ø 13 x 4	105	4x45°	1,09
298 065 135 110	65	135	15,5	ø 13 x 4	110	4x45°	1,26
298 070 142 117	70	142	16,5	ø 13 x 4	117	5x45°	1,50
298 073 145 120	73	145	16,5	ø 13 x 4	120	5x45°	1,50
298 075 152 125	75	152	16,5	ø 13 x 4	125	5x45°	1,68
298 080 162 127	80	162	16,5	ø 15 x 4	127	5x45°	1,94
298 090 175 145	90	175	18,5	ø 15 x 4	145	5x45°	2,44
298 095 181 149	95	181	18,5	ø 17 x 6	149	7x45°	2,53
298 100 188 155	100	188	18,5	ø 17 x 6	155	7x45°	2,81
298 105 188 156	105	188	24,5	ø 17 x 6	156	8x45°	3,44
298 115 194 162	115	194	24,5	ø 17 x 6	162	8x45°	3,47
298 123 228 190	123	228	28,0	ø 21 x 6	190	8x45°	5,93
298 138 240 200	138	240	28,0	ø 21 x 6	200	8x45°	6,05
298 143 250 210	143	250	28,0	ø 21 x 6	210	8x45°	6,65
298 158 280 230	158	280	33,0	ø 23 x 6	230	10x45°	9,98
298 168 300 250	168	300	38,0	ø 25 x 6	250	12x45°	13,24
298 178 325 270	178	325	38,0	ø 28 x 6	270	12x45°	15,84

MATERIAL: STAHL S355J0 (Fe510C)